

Bitzer 4H.2

Specifications

Marca	Bitzer
Tipo	4H.2
Refrigerante	Freon
kW at 0°C/+40°C	54,8
kW at -5°C/+40°C	45,7
kW at -10°C/+40°C	37,7
kW at -20°C/+40°C	24,8
kW at -30°C/+40°C	15,3
kW at -40°C/+40°C	8,4
Electromotor Specs	15 kW at 1460 RPM
Piston Descargador	✓
Sober Bancada	✓
Presostatos	✓
Manómetros de Presion	✓
Recipiente de líquido	✓
La línea de líquido filtro secador	✓
Mirilla	✓
Panel de control	✓
Comentarios	# // Electromotor: 15 kW at 1460 RPM // Pully EM: 200 mm / Pully compr.: 220 mm
Comentarios	R404a - R22 or other freon types
Tamaños	1650x1200x2200 mm (LxWxH)



Stock

1

Description

Used Bitzer 4H.2

Used Bitzer 4H.2 freon compressor, complete with unloaded start, pressure safety switches, pressure gauges, liquid receiver, liquid line filter drier, sight glass and control panel. This unit has a cooling capacity of 54,8 kW at 0°C/+40°C.

Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and deliver after an industrial cleaning. *If requested we are happy to arrange your logistics.





