

Bitzer 4H.2 / 6G.2 / 6F.2

Specifications

Marca	Bitzer
Tipo	4H.2 / 6G.2 / 6F.2
Refrigerante	Freon
kW at -10°C/+40°C	190
kW at -20°C/+40°C	124,5
kW at -30°C/+40°C	76,2
kW at -40°C/+40°C	41,5
Electromotor Specs	16 / 30 / 37
Piston Descargador	✓
Sober Bancada	✓
Presostatos	✓
Manómetros de Presion	✓
Recipiente de Líquido	✓
Recipiente de Líquido ltr.	20
Separador de aceite	✓
La línea de líquido filtro	✓
secador	
Panel de control	✓
Comentarios	# // Electromotor 16 kW at 1445 RPM (4H.2) // 30 kW at 1475 RPM (6H.2) // 37 kW at 1480 RPM (6F.2) // Evaporator Helpman PLV 24-4
Comentarios	R404a - R22 or other freon types



	(LxWxH)
Dimensions	3900x1700x2500 mm

Description

Used Bitzer 4H.2 / 6G.2 / 6F.2

Used Bitzer 4H.2 / 6G.2 / 6F.2 freon compressor rack, complete with unloaded start, pressure safety switches, pressure gauges, oil separator, liquid line filter drier, control panel and liquid receiver with a volume of 20 liters.

Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and deliver after an industrial cleaning. *If requested we are happy to arrange your logistics.







