

Bitzer 4G.2 (x3) / 6F.2 (x1)

Specifications

Marca	Bitzer
Tipo	4G.2 (x3) / 6F.2 (x1)
Refrigerante	Freon
kW at +10°C/+40°C	465,2
kW at 0°C/+40°C	303,4
kW at -5°C/+40°C	268,6
kW at -10°C/+40°C	219,5
kW at -20°C/+40°C	140,9
kW at -30°C/+40°C	84
kW at -40°C/+40°C	43,8
Electromotor Specs	22 / 37
Piston Descargador	✓
Control de capacidad	✓
Sober Bancada	✓
Presostatos	✓
Manómetros de Presion	✓
Separador de aceite	✓
Comentarios	# // 1x Compr. Bitzer 4G.2 y.o.b. 2007 // Electromotor 4G.2: 22 kW at 1480 RPM // Electromotor 6F.2: 37 kW at 1475 RPM
Comentarios	R404a - R22 or other freon types
Package / Rack	✓



	(LxWxH)
Dimensions	3800x1350x1950 mm

Description

Used Bitzer 4G.2 (x3) / 6F.2 (x1)

Used Bitzer 4G.2 (x3) / 6F.2 (x1) freon compressor rack, complete with unloaded start, capacity control, pressure safety switches, pressure gauges and oil separator. this unit has a cooling capacity of 465,2 kW at +10°C/+40°C.

Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and deliver after an industrial cleaning. *If requested we are happy to arrange your logistics.





