

## Bitzer 6F.2 (x3)

### Specifications

Marca	Bitzer
Tipo	6F.2 (x3)
Refrigerante	Freon
kW at +10°C/+40°C	497,7*
kW at 0°C/+40°C	382
kW at -5°C/+40°C	317,1
kW at -10°C/+40°C	260,9
kW at -20°C/+40°C	170
kW at -30°C/+40°C	103,2
kW at -40°C/+40°C	55,5
Electromotor Specs	37
Piston Descargador	✓
Control de capacidad	✓
Sober Bancada	✓
Presostatos	✓
Manómetros de Presion	✓
Recipiente de líquido	✓
Recipiente de líquido ltr.	30
Separador de aceite	✓
La línea de líquido filtro secador	✓
Mirilla	✓
Panel de control	✓
Comentarios	# // *Capacity based on +7,5C/+40C // Electromotor: 37 kW at 1475 RPM // DX Unit



Comentarios	R404a - R22 or other freon types
Package / Rack	✓
Tamaños	2900x1500x1750 mm (LxWxH)
Stock	1

## Description

### Used Bitzer 6F.2 (x3)

Used Bitzer 6F.2 (x3) freon compressor rack, complete with unloaded start, capacity control, pressure safety switches, pressure gauges, oil separator, liquid line filter drier, sight glass, control panel and liquid receiver with a volume of 30 liters.

Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.  
\*Optional we can also perform a new paint job and arrange the logistics.









