

## **Grasso RC 412E**

### **Specifications**

| Marca                 | Grasso                   |
|-----------------------|--------------------------|
| Tipo                  | RC 412E                  |
| Refrigerante          | NH 3 (ammonia)           |
| kW at 0°C/+40°C       | 450                      |
| kW at -5°C/+40°C      | 383,7*                   |
| Electromotor Specs    | 160                      |
| Piston Descargador    | 1                        |
| Control de capacidad  | 1                        |
| Sober Bancada         | 1                        |
| Presostatos           | 1                        |
| Manometros de Presion | 1                        |
| Separador de aceite   | 1                        |
| Comentarios           | y.o.b. 2000 // *Capacity |
|                       | based on -6C/+36C        |
| Package / Rack        | 1                        |
| Stock                 | 1                        |
|                       |                          |



### **Description**

### **Used Grasso RC 412E**

Used compressor unit GEA Grasso RC 412E. This NH3 ammonia compressor unit has the following components: 1x Electromotor Schorch KN7315S-BB01B-401 (160 kW at 1480 RPM) and GEA Grasso Oil separator. Part of complete installation, see stocknumber: 7236 \*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. \*Optional we can also perform a new paint job and arrange the logistics.



































# Your partner for used commercial and industrial refrigeration equipment

1.1.2 Twee compress
Zuigercompressor.
Fabrikaat
Type
Koelcapaciteit
Opganomen vermogen
Verdampingstemperatuur
Condensatietemperatuur
Toerental
Capaciteitsregeling

Inclusief:

Elektromotor. Vermogen Toerental Fabrikaat : 160 kW. : 1.450 omw./min. : Leroy Somer.

- Instrumenten paneel.

  Zuig, pers en oliedrukmanometer.
  Hoge en lagedruk pressostaat.
  Oliedrukpressostaat.
  Persgastemperatuurbeveiliging.

Frame.

De compressor is met de elektromotor, de olie afscheider en toebehoren samengebouwd op een stalen frame.

Het frame is gestraald en in kleur gespoten.

**HOS BV** info@hosbv.com (+31) (0)23-5404237 www.hosbv.com