

## Bitzer HSN 6451-40

### Specifications

|                      |                                  |
|----------------------|----------------------------------|
| Marca                | Bitzer                           |
| Tipo                 | HSN 6451-40                      |
| Refrigerante         | Freon                            |
| kW at -10°C/+40°C    | 65*                              |
| kW at -20°C/+40°C    | 52,2                             |
| kW at -30°C/+40°C    | 32,3                             |
| kW at -40°C/+40°C    | 18,7                             |
| Piston Descargador   | ✓                                |
| Control de capacidad | ✓                                |
| Comentarios          | serial 16070328 = used condition |
| Tamaños              | 930x500x440 mm<br>(LxWxH)        |
| Stock                | 1                                |



### Description

#### Used Bitzer HSN 6451-40

Used Semi-hermetic Screw Compressor  
Bitzer HSN 6451-40 . Overhauled! As good as new



Typ HSN 6451-40  
S.Nr. 16070328

BITZER KÜHLMASCHINENBAU GMBH  
Made in E.C.

| Nennspannung<br>V 3Ph~ | Frequ.<br>Hz | Betr.strom<br>A (max.) | Anlaufstrom<br>A (Δ) | A (ΔΔ) | Fördervol.<br>m³/h | Drehzahl<br>min⁻¹ |
|------------------------|--------------|------------------------|----------------------|--------|--------------------|-------------------|
| 400                    | 50           | 65                     | 187                  | 313    | 140                | 2900              |
| 460                    | 60           | 65                     | 187                  | 313    | 168                | 3500              |

IP 54 ND/HD max. 19 / 28 bar

Typ HSN 6451-40  
S.Nr. 15660039

BITZER KÜHLMASCHINENBAU GMBH  
Made in E.C.

| Nennspannung<br>V 3Ph~ | Frequ.<br>Hz | Betr.strom<br>A (max.) | Anlaufstrom<br>A (Y) | A (YY) | Fördervol.<br>m³/h | Drehzahl<br>min⁻¹ |
|------------------------|--------------|------------------------|----------------------|--------|--------------------|-------------------|
| 400                    | 50           | 65                     | 187                  | 313    | 140                | 2900              |

IP 54 ND/HD max. 19 / 25 bar