

Thermotec PA05 / H35CC

Specifications

Brand	Thermotec
Type	PA05 / H35CC
Product type	Air Cooled Chiller
Capacité kW	27,6
Capacity Tons	7,8
Réfrigérant	Freon
Refrigerant Type	R407C
Liquid buffer tank	✓
Pump	✓
Weight	580
Sizes	2060x870x2000 mm (LxWxH)
Compressor(s) type & model	Bristol H75Q144DBEE
Display	Carel pGD
Number of fans	2
Fan specifications	1,1 kW - 910 RPM
Stock	1



Description

Used Thermotec PA05 / H35CC

In good condition air cooled chiller Thermotec PA05 / H35CC series 08C021. Complete with 1 Bristol H75G144DBEE scroll compressor. 2 Nicotra fans with 1,1 kW - 910 RPM. Liquid buffer tank 420 ltr and a Grundfos CHI8-30 pump with a rated flow of 7,5 m3/h. Capacity based on 0°C/+40°C.

*All components of this used chiller will be tested on good working, leak free condition (condensing blocks), compressors, fans, control panel, etcetera). Choosing HOSBV means buying with warranty. We perform a industrial cleaning and rust spots will be covered. Also, we can arrange your shipment.



Manufactured by				
Thermotec		CE		
Luipegem 146b - B -2880 Bornem Tel. +32-3-7405030 -- Fax. +32-3-7405039 -- URL - Thermotec.be				
Data	Model + Version		PA05/H35CC	
	Series		08C021	
	Weight		580	Kg
	Ref.code PA*-05P009-E35004-15_RV			
Refrigerant EN 378	Refrigerant		R407C	
	Number of equal circuits		1	
	Refrigerant fill weight / circuit		15	Kg
	Max allowable pressure	HP	2800	KPa
		LP	2000	KPa
PED category		-		
Transfer Medium EN 13445	Fluid		Water	
	Allowable temperature	Max.	30	°C
		Min.	3	°C
	Volume tank		420	Liter
	Allowable tank pressure	Max.	600	KPa
		Min.	-20	KPa
	Rated pump flow		10	m³/h
Rated height		15.8	m	
Electrical data EN 60204	Voltage		3x 380/415V 50 Hz	
	Rated Electrical power		11.9	Kw
	Max. Electrical current		36	Amp
	Protection class		IP54	





