

Bitzer 4G.2Y (x1) & 4G.2 (x1)

Specifications

Marque	Bitzer
Le type	4G.2Y (x1) & 4G.2 (x1)
Réfrigérant	Freon
kW at 0°C/+40°C	141,8
kW at -5°C/+40°C	117,5
kW at -10°C/+40°C	96,3
kW at -20°C/+40°C	62,4
kW at -30°C/+40°C	37,7
kW at -40°C/+40°C	20,2
Démarrage à vide	✓
Contrôle de capacité	✓
Sur le châssis en acier	✓
Interrupteurs de sécurité	✓
de pression	
Manomètres	✓
Séparateur d'huile	✓
Voyant	✓
Electrovanne	✓
m ³ / h	204
Remarques	Y.o.b. 1996 - 4G.2 & Y.o.b. 2010 - 4G.2Y
Package / Rack	✓
Tailles	1200x1100x750 mm (LxWxH)
Stock	1



Description

Used Bitzer 4G.2Y (x1) & 4G.2 (x1)

Used Bitzer open-type reciprocating with 4G.2 & 4G.2Y compressors on Freon. Complete with a Rotor XC160L04 electric motor (x2) - 50 Hz - 15 kW - 1460 RPM, AC&R S-5692X oil separator, pressure and safety switches/gauges and sight glass. The compressors has a displacement of 204 m³/h at 1750 RPM.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment solely if it has passed our extensive quality test and after it has been cleaned industrially. *If requested we are happy to arrange your shipment.









