

Bitzer 4V-10.2

Specifications

Marque	Bitzer
Le type	4V-10.2
Réfrigérant	Freon
kW at 0°C/+40°C	26,8
kW at -5°C/+40°C	22,2
kW at -10°C/+40°C	18,2
kW at -20°C/+40°C	11,8
kW at -30°C/+40°C	7,1
kW at -40°C/+40°C	3,7
Démarrage à vide	✓
Sur le châssis en acier	✓
Interrupteurs de sécurité de pression	✓
Réservoir de liquide	✓
Séparateur d'huile	✓
Voyant	✓
Electrovanne	✓
Panneau de configuration	✓
m3 / h	33,07
Weight	142 kg
Tailles	1000x610x1040 mm (LxWxH)
Stock	1



Description

Used Bitzer 4V-10.2

Used Bitzer 4V-10.2 semi-hermetic reciprocating compressor on steel base frame. Complete with a pressure and safety switch, liquid receiver, oil separator, sight glass and control panel. The compressor has a displacement of 33,07 m³/h at 1450 RPM and 39,91 m³/h at 1750 RPM.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also perform a new paint job and arrange the logistics.



