

Bitzer 4MTC-10K-40S (x1) & 4JTC-10K-40P (x1)

Specifications

Marque	Bitzer
Le type	4MTC-10K-40S (x1) & 4JTC-10K-40P (x1)
Réfrigérant	CO2
kW at 0°C/+40°C	39,2
kW at -5°C/+40°C	32,3
kW at -10°C/+40°C	24,1
Sur le châssis en acier	✓
Manomètres	✓
Commutateurs de pression de condensation	✓
Réservoir de liquide	✓
Réservoir de liquide ltr.	66
Liquid déshydrateur ligne	✓
Voyant	✓
Panneau de configuration	✓
m3 / h	50 Hz - 15,7 m³/h / 60 Hz - 18,8 m³/h
Remarques	Y.o.b. 2018
Tailles	2000x810x2100 mm (LxWxH)
Stock	1



Description

Used Bitzer 4MTC-10K-40S (x1) & 4JTC-10K-40P (x1)

Used Epta ECOS compressor unit on R744 (CO2) built in 2018. Complete with 1 Bitzer 4MTC-10K-40S & 1 4JTC-10K-40P Semi-hermetic reciprocating compressors, Legnago FL66+2SGR7K+M28+2SV(M28/M28) liquid receiver with a volume of 66 liters, control cabinet with a Power Electronics SD300 frequency converter, Frigolink Animus ANI-1F5 process controller and a Carel EVD evolution. The compressors have a total displacement of 15,7 m³/h at 50 Hz and 18,8 m³/h at 60 Hz. Further this set comes with a Güntner GGHV CD 080.2MF/12E-39 CO2 cooler. Complete with 2 EBM-Papst S3G800-CD57-39

fans - 50/60 Hz - 0,48 kW - 630 RPM -
diameter 800 mm.

*Why choose for HOSBV? We are not
only the largest used refrigeration
specialist in Europe, but also, we
deliver all equipment solely if it has
passed our extensive quality test and
after it has been cleaned industrially.

*If requested we are happy to arrange
your shipment.



EPTA Deutschland GmbH Ludolf-Krehl-Str. 7 - 11 68167 Mannheim Tel. 0621-1281-0 Hersteller / Lieferer // Manufacturer / Supplier			
Serien- Nr. Serial No.		300200214538-1	
Auftrag / Typ Order or Model No.		Aldi Nord Göttingen NK	
Herstelljahr Year of		2018	R744
Kältemittel Füllmenge // Refrigerant Charge		60	kg
max. zulässiger Druck ND/HD max. allowable Pressure LP/HP		45 / 120	bar
Prüfdruck ND / HD Test Pressure LP / HP		64,35 / 132	bar
Betriebsspannung // operating voltage		400 V / 3 ~ / 50 Hz	
Steuerspannung // control voltage		230 V / 1 ~ / 50 Hz	
max. Betriebsstrom // max. operating current		43,00	A











