

Helpman HTC 100-122-V/ 420 PREP

Specifications

La marque	Helpman
Le type	HTC 100-122-V/ 420 PREP
Type de produit	Drycooler
Capacité kW	133,7*
Nombre de ventilateurs	2
RPM de fans	420/310
Réfrigérant	Glycol
Le débit d'air in m³/h	38.000
diamètre fans Ø	1000 mm
Surface (m2)	304
Volume du tube	25 dm³
Tailles	4150x1250x1450 mm (LxWxH)
Poids	502 kg
Remarques	Y.o.b. 2002
Remarks	*Capacity is based on a medium inlet temperature of 60°C and an outlet temperature of 40°C
Stock	1



Description

Used Helpman HTC 100-122-V/ 420 PREP

Used Helpman HTC 100-122-V drycooler. Complete with 2 Ziehl-Abegg FE100-NDS.6N.V7 fans - 50 Hz - 0,87/0,49 kW - 430/310 RPM - diameter 1000 mm and a total airflow of 38.000 m³/h.

The current condenser will be converted into a drycooler and the appropriate flanges will be installed. The drycooler has a capacity of 133,7kW with a medium inlet temperature of 60°C and an outlet temperature of 40°C.

*All components of this used condenser will be tested on adequate functionality, leak free condition (electro engines), condensing block,



bearings. Choosing HOSBV means buying with warranty. We perform an industrial cleaning on demand, we can arrange your shipment.



HELPMAN		Apparatenfabriek Helpman B.V. Peizerweg 97, 9727 AJ Groningen (NL) Tel. ++31 50 5217555 / Fax ++31 50 5264873 info@helpman.com / www.helpman.com	
Type	HTC 100.122-V/420 PREP		
Serial number	511292/120964-15944/01		
Refrigerant	R404A		
Operating temp.	100	°C (min/max)	
Design/test pressure	22/28	bar	year 2002
Internal volume	25.0	dm³	
Weight (empty)	502	kg	0134 



