

# Bitzer 6G-40.2Y-40P

## Specifications

Marque	Bitzer
Le type	6G-40.2Y-40P
Réfrigérant	Freon
kW at 0°C/+40°C	102,6
kW at -5°C/+40°C	85,4
kW at -10°C/+40°C	70,3
kW at -20°C/+40°C	46,0
kW at -30°C/+40°C	28,0
kW at -40°C/+40°C	14,9
Sur le châssis en acier	✓
Interrupteurs de sécurité de pression	✓
Manomètres	✓
Réservoir de liquide	✓
Réservoir de liquide ltr.	160 l
Séparateur d'huile	✓
Liquid déshydrateur	✓
ligne	
Voyant	✓
m <sup>3</sup> / h	50 Hz - 126,8 m <sup>3</sup> /h / 60 Hz - 152,9 m <sup>3</sup> /h
Remarques	Y.o.b. 2003
Tailles	1400x870x2420 mm (LxWxH)
Stock	1



## Description

### Used Bitzer 6G-40.2Y-40P

Used Bitzer 6G-40.2Y-40P semi-hermetic reciprocating compressor unit. Complete with a Bitzer FS1602 liquid receiver with volume of 160 liters, Henry Technologies S-5694-CE oil separator, pressure and safety switches/gauges, Danfoss liquid line filter drier and a sight glass. The displacement of the compressor is 126,8 m<sup>3</sup>/h at 50 Hz and 152,9 m<sup>3</sup>/h at 60 Hz.

\*Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and an industrial cleaning.

\*Optionally we can also perform a new paint job and arrange the logistics.





