

Bitzer 4H-25.2Y-40P Condensing unit

Specifications

Marque	Bitzer
Le type	4H-25.2Y-40P Condensing unit
Réfrigérant	Freon
kW at 0°C/+40°C	59,4
kW at -5°C/+40°C	49,4
kW at -10°C/+40°C	40,6
kW at -20°C/+40°C	26,4
kW at -30°C/+40°C	15,9
kW at -40°C/+40°C	8,3
Sur le châssis en acier	✓
Interrupteurs de sécurité de pression	✓
Manomètres	✓
Réservoir de liquide	✓
Réservoir de liquide ltr.	50
Aspiration d'accumulateur	✓
Séparateur d'huile	✓
Liquid déshydrateur ligne	✓
Voyant	✓
m ³ / h	73,7 m ³ /h - 88,9 m ³ /h
Remarques	Y.o.b. 2013
Condensing Unit	✓
Tailles	2450x1100x2350 mm (LxWxH)



Stock

7

Description

Used Bitzer 4H-25.2Y-40P Condensing unit

Used Fredvic UM 250 MT/S condensing unit on Freon. Complete with 1 Bitzer 4H-25.2Y-40P semi-hermetic reciprocating compressor, condenser with 2 EBM-Papst fans, suction accumulator, OCS liquid receiver with a volume of 50 liter, Frigo-Mec SO/ER-33 oil separator, liquid line filter drier, pressure and safety switches/gauges and a control cabinet. The compressor has a displacement of 73,7 m³/h at 50 Hz & 88,9 m³/h at 60 Hz.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also arrange the logistics.









