

# Bitzer HSK 7451-70-40P (x2) Condensing unit

## Specifications

Marque	Bitzer
Le type	HSK 7451-70-40P (x2) Condensing unit
Réfrigérant	Freon
kW at 0°C/+40°C	345,5
kW at -5°C/+40°C	284,2
kW at -10°C/+40°C	231,7
kW at -20°C/+40°C	149,2
Démarrage à vide	✓
Contrôle de capacité	✓
Sur le châssis en acier	✓
Interrupteurs de sécurité de pression	✓
Manomètres	✓
Réservoir de liquide	✓
Réservoir de liquide ltr.	200
Séparateur d'huile	✓
Voyant	✓
Electrovanne	✓
m <sup>3</sup> / h	384 m <sup>3</sup> /h at 50 Hz & 460 m <sup>3</sup> /h at 60 Hz
Remarques	Y.o.b. 2013
Condensing Unit	✓
Tailles	6750x2200x2420 mm (LxWxH)



Stock

3

## Description

### **Used Bitzer HSK 7451-70-40P (x2) Condensing unit**

Used Fredvic UMC 2x700 VSMT condensing unit on Freon. Complete with 2 Bitzer HSK 7451-70-40P semi-hermetic screw compressors, condenser with 4 EBM-Papst A6D800-AD01-01 fans - 50 Hz - 1,94/1,21 kW - 880/670 RPM - diameter 800 mm, Frigo-Mec liquid receiver, Bitzer oil separator, brazed heat exchanger for heat recovery, ABB ACH550-01-125A-4+B055 frequency converter and a control cabinet with a Carel controller. The compressors have a total displacement of 384 m<sup>3</sup>/h at 50 Hz & 460 m<sup>3</sup>/h at 60 Hz.

\*Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

\*Optional we can also arrange the logistics.











