

# Bitzer 6F-50.2Y-40P Condensing unit

## Specifications

Marque	Bitzer
Le type	6F-50.2Y-40P Condensing unit
Réfrigérant	Freon
kW at 0°C/+40°C	121,7
kW at -5°C/+40°C	101,3
kW at -10°C/+40°C	83,6
kW at -20°C/+40°C	55,0
kW at -30°C/+40°C	33,9
kW at -40°C/+40°C	18,6
Sur le châssis en acier	✓
Interrupteurs de sécurité de pression	✓
Manomètres	✓
Réservoir de liquide	✓
Réservoir de liquide ltr.	70
Aspiration d'accumulateur	✓
Séparateur d'huile	✓
Liquid déshydrateur ligne	✓
Voyant	✓
Panneau de configuration	✓
m3 / h	151,6 m <sup>3</sup> /h at 50 Hz & 183 m <sup>3</sup> /h at 60 Hz
Remarques	Y.o.b. 2013



Condensing Unit	✓
Tailles	3240x1100x2320 mm (LxWxH)
Stock	3

## Description

### Used Bitzer 6F-50.2Y-40P Condensing unit

Used Fredvic UM 500 MT/S condensing unit on Freon. Complete with a Bitzer 6F-50.2Y-40P semi-hermetic reciprocating compressor, condenser with 3 EBM-Papst fans - 50 Hz - 1,94/1,21 kW - 880/670 RPM, OCS liquid receiver with a volume of 70 liter, suction accumulator, oil separator, liquid line filter drier, pressure and safety switches/gauges and a control cabinet. The compressor has a displacement of 151,6 m<sup>3</sup>/h at 50 Hz & 183 m<sup>3</sup>/h at 60 Hz.

\*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

\*Optional we can also arrange the logistics.







