

Bitzer 4EC-4.2Y-40S Condensing unit

Specifications

| | |
|---------------------------------------|--|
| Marque | Bitzer |
| Le type | 4EC-4.2Y-40S Condensing unit |
| Réfrigérant | Freon |
| kW at -5°C/+40°C | 14,4 |
| kW at -10°C/+40°C | 11,9 |
| kW at -20°C/+40°C | 7,7 |
| kW at -30°C/+40°C | 4,7 |
| kW at -40°C/+40°C | 2,4 |
| kW at -45°C/+40°C | 1,6 |
| Sur le châssis en acier | ✓ |
| Interrupteurs de sécurité de pression | ✓ |
| Réservoir de liquide | ✓ |
| Réservoir de liquide ltr. | 13 |
| Voyant | ✓ |
| Panneau de configuration | ✓ |
| m3 / h | 22,7 m ³ /h at 50 Hz & 27,4 m ³ /h at 60 Hz |
| Remarques | Y.o.b. 2007 |
| Condensing Unit | ✓ |
| Tailles | 1510x830x680 mm (LxWxH) |
| Stock | 1 |



Description

Used Bitzer 4EC-4.2Y-40S Condensing unit

Used Condensing unit on Freon. Complete with a Bitzer 4EC-4.2Y-40S semi-hermetic reciprocating compressor, Condenser with 1 fan, Frigo-mec RV-220x427 liquid receiver with a volume of 13 liter, pressure and safety switch, liquid line filter drier and a control cabinet. The compressor has a displacement of 22,7 m³/h at 50 Hz & 27,4 m³/h at 60 Hz.

*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning. *If requested we are happy to arrange your logistics.



