

Bock HGX12P/60-4 S Water-cooled condensing unit

Specifications

| | |
|---------------------------------------|--|
| Marque | Bock |
| Le type | HGX12P/60-4 S Water-cooled condensing unit |
| Réfrigérant | Freon |
| Refrigerant type | R410A |
| kW at +10°C/+40°C | 8,8* |
| kW at 0°C/+40°C | 6,0* |
| kW at -5°C/+40°C | 4,9* |
| kW at -10°C/+40°C | 4,0* |
| kW at -20°C/+40°C | 2,4* |
| kW at -30°C/+40°C | 1,8* (-25°C/+40°C) |
| Sur le châssis en acier | ✓ |
| Interrupteurs de sécurité de pression | ✓ |
| Manomètres | ✓ |
| Liquid déshydrateur ligne | ✓ |
| Voyant | ✓ |
| Panneau de configuration | ✓ |
| m3 / h | 5,4 at 50 Hz |
| Remarques | *Capacity based on Freon type: R410a |
| Condensing Unit | ✓ |



(LxWxH)

Stoeltes

Ø10x930x1550 mm

Description

Used Bock HGX12P/60-4 S Water-cooled condensing unit

Used Bock water-cooled condensing unit on Freon. Complete with a Bock HGX12P/60-4 S semi-hermetic compressor, Bitzer K073H shell and tube condenser, liquid line filter drier, pressure and safety switches/gauges, sight glass and a control cabinet with a Merkury Mk3 8-2/5M display. The compressor has a displacement of 5,4 m³/h at 50 Hz.

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and deliver after an industrial cleaning. *If requested we are happy to arrange your logistics.





