

Bitzer 4PES-10Y-40P (x1) & 4NES-14Y-40P (x2) Compressor unit

Specifications

Marque	Bitzer
Le type	4PES-10Y-40P (x1) & 4NES-14Y-40P (x2) Compressor unit
Réfrigérant	Freon
kW at 0°C/+40°C	82,3
kW at -5°C/+40°C	65,5
kW at -10°C/+40°C	51,4
kW at -20°C/+40°C	29,4
Interrupteurs de sécurité de pression	✓
Manomètres	✓
Séparateur d'huile	✓
Système de niveau d'huile	✓
Liquid déshydrateur ligne	✓
Voyant	✓
Panneau de configuration	✓
m ³ / h	161,1
Remarques	Y.o.b. 2014
Package / Rack	✓
Tailles	2300x1400x1400 mm (LxWxH)



Stock

1

Description

Used Bitzer 4PES-10Y-40P (x1) & 4NES-14Y-40P (x2) Compressor unit

Used Rivacold RV4C1103-1 compressor unit on Freon. Complete with a Bitzer 4PES-10Y-40P (x1) & 4NES-14Y-40P (x2) semi-hermetic reciprocating compressors, Ocs cold OCS-08 oil reservoir, Henry Technologies S-1901-CE oil separator, pressure and safety switches/gauges and a control cabinet with a Carel pR100 controller and Carel display. The compressors have a total displacement of 161,1 m³/h. The capacity is based on the use of Freon type: R134A.

*Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also perform a new paint job and arrange the logistics.



RIVACOLD
 Via Stella,7 - Montecchio 61022 Vallefoglia(PU)ITALY
 Tel. +39 - 0721 - 919911 r.a. Fax +39 - 0721 - 480015
 Internet:www.rivacold.com Mail:info@rivacold.com

CE

Code : **RV4C1103 - 1**

Volt/Ph/Hz : 400/3/50	Comp. : 4NES - 14Y 4PES
W : 46950	HP : 14X2 10X1
Win : 22620	In (A) : 43.57

W defrost :

Gas : R134A	Kg :
PS Hp : 20 bar	PS Lp : 14 bar
TS Hp : -10/100 °C	TS Lp : -40/100 °C

S/N : **14401384**

Direttiva 97/23/CE del 29.05.1997 (P.E.D.) Cat. III - Prodotto nel 20/14

0948 0 060144 013843









