

Bitzer 4TCS-12.2Y-40P (x2) Condensing unit

Specifications

| | |
|---------------------------|--|
| Marque | Bitzer |
| Le type | 4TCS-12.2Y-40P (x2) Condensing unit |
| Réfrigérant | Freon |
| kW at 0°C/+40°C | 64,2 |
| kW at -5°C/+40°C | 52,1 |
| kW at -10°C/+40°C | 41,8 |
| kW at -20°C/+40°C | 25,7 |
| kW at -30°C/+40°C | 14,5 |
| Contrôle de capacité | ✓ |
| Réservoir de liquide | ✓ |
| Réservoir de liquide ltr. | 80 |
| Séparateur d'huile | ✓ |
| Liquid déshydrateur | ✓ |
| ligne | |
| Voyant | ✓ |
| Panneau de configuration | ✓ |
| m3 / h | 82,6 |
| Remarques | Y.o.b. 2011 |
| Condensing Unit | ✓ |
| Tailles | 4100x1300x2200 mm (LxWxH) |
| Stock | 1 |



Description

Used Bitzer 4TCS-12.2Y-40P (x2) Condensing unit

Used Rivacold RV4C0280-2 condensing unit on Freon. Complete with a Bitzer x2 4TCS-12.2Y-40P semi-hermetic reciprocating compressors, condenser with 3 Ziehl-Abegg FE080-NDS.6K.V7 fans - 50 Hz - 0,37/0,20 kW - 440/340 RPM, Frigo Mec 324/1113VKO1-FSR liquid receiver, OCS RLTU23 liquid receiver, Henry Technologies S-5690 oil separator, OCS-08 RLTU8 oil reservoir, 2 Danfoss frequency regulators and a control cabinet with a 2 Danfoss controllers and 2 Danfoss displays. The compressors have a total displacement of 82,6 m³/h at 50 Hz and 99,8 m³/h at 60 Hz.

*Why choose for HOSBV? Were not only



the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also perform a new paint job and arrange the logistics.











