

Bitzer 4H-15.2Y-40P (x3) & 4J-13.2Y-40P (x2)

Specifications

| | |
|--|---|
| Marque | Bitzer |
| Le type | 4H-15.2Y-40P (x3) & 4J-13.2Y-40P (x2) |
| Réfrigérant | Freon |
| Refrigerant type | R507 |
| kW at -5°C/+40°C | 153,0/87,6* |
| kW at -10°C/+40°C | 126,6/72,2* |
| kW at -20°C/+40°C | 83,7/47,6* |
| kW at -30°C/+40°C | 52,0/29,2* |
| kW at -40°C/+40°C | 29,2/15,9* |
| kW at -45°C/+40°C | 20,4/10,8* |
| Sur le châssis en acier | ✓ |
| Interrupteurs de sécurité de pression | ✓ |
| Manomètres | ✓ |
| Commutateurs de pression de condensation | ✓ |
| Voyant | ✓ |
| Panneau de configuration | ✓ |
| m ³ / h | Cooling: 50 Hz - 221,1 m ³ /h / 60 Hz 266,7 Freezing: 50 Hz - 127,0 m ³ /h / 60 Hz - 153,4 m ³ /h |



| | |
|----------------|-----------------------------|
| Remarques | Y.o.b. 2007 |
| Package / Rack | ✓ |
| Tailles | 3200x800x1950 mm (LxWxH) |
| Stock | 1 |

Description

Used Bitzer 4H-15.2Y-40P (x3) & 4J-13.2Y-40P (x2)

Used Profroid VZP330-4010SAT2 central cooling and freezing installation on Freon. Complete with 3 Bitzer 4H-15.2Y-40P (Cooling) & 2 Bitzer 4J-13.2Y-40P (Freezing) semi-hermetic reciprocating compressors, brazed heat exchanger for heat recovery, pressure and safety switches and a control cabinet with Danfoss controllers. The cooling compressors have a total displacement of 221,1 m³/h at 50 Hz & 266,7 m³/h at 60 Hz and the freezing compressors have a displacement of 50 Hz - 127 m³/h & 153,4 m³/h at 60 Hz. *Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and an industrial cleaning. *Optionally we can also perform a new paint job and arrange the logistics.









