

# Bitzer 6F-40.2Y-40P (x3) & 4J-13.2Y-40P (x1)

## Specifications

Marque	Bitzer
Le type	6F-40.2Y-40P (x3) & 4J-13.2Y-40P (x1)
Réfrigérant	Freon
Refrigerant type	R404A
kW at -5°C/+40°C	345,5
kW at -10°C/+40°C	284,5
kW at -20°C/+40°C	185,9
kW at -30°C/+40°C	113,0
kW at -40°C/+40°C	60,3
Sur le châssis en acier	✓
Interrupteurs de sécurité de pression	✓
Manomètres	✓
Réservoir de liquide	✓
Réservoir de liquide ltr.	228
Séparateur d'huile	✓
Système de niveau d'huile	✓
Liquid déshydrateur ligne	✓
Voyant	✓
Electrovanne	✓
m3 / h	518,3
Remarques	Y.o.b. 2008



---

Tailles	330x1360x2060 mm (LxWxH)
Stock	1

---

## Description

### **Used Bitzer 6F-40.2Y-40P (x3) & 4J-13.2Y-40P (x1)**

Used Bitzer 6F-40.2Y-40P (x3) & 4J-13.2Y-40P (x1) semi-hermetic reciprocating compressor rack on Freon. Complete with a Bitzer F2202N liquid receiver with a volume of 228 liters, Henry Technologies S-5203-CE oil separator, Henry Technologies S-9109-CE oil reservoir, brazed heat exchanger, pressure and safety switches/gauges and a liquid line filter drier. The compressors have a displacement of 518,3 m<sup>3</sup>/h at 50 Hz. \*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and an industrial cleaning. \*Optionally we can also perform a new paint job and arrange the logistics.







