

Bitzer 4FE-28Y-40P Condensing unit

Specifications

Marque	Bitzer
Le type	4FE-28Y-40P Condensing unit
Réfrigérant	Freon
kW at 0°C/+40°C	84,4
kW at -5°C/+40°C	70,5
kW at -10°C/+40°C	58,4
kW at -20°C/+40°C	38,7
kW at -30°C/+40°C	24,2
kW at -40°C/+40°C	13,6
kW at -45°C/+40°C	9,6
Contrôle de capacité	✓
Sur le châssis en acier	✓
Interrupteurs de sécurité de pression	✓
Réservoir de liquide	✓
Réservoir de liquide ltr.	47,2
Liquid déshydrateur ligne	✓
Voyant	✓
Electrovanne	✓
Panneau de configuration	✓
m3 / h	50 Hz - 101,8 m ³ /h & 60 Hz - 121,3 m ³ /h
Remarques	Y.o.b. 2017
Condensing Unit	✓



Tailles	2500x1000x1900 mm (LxWxH)
Stock	1

Description

Used Bitzer 4FE-28Y-40P Condensing unit

Used Bitzer condensing unit on Freon. Complete with Bitzer 4FE-28Y-40P semi-hermetic reciprocating compressor, condenser with 8 EBM-Papst S4E400-AP02-83 fans - 50/60 Hz - 0,16/0,24 kW - 1430/1700 RPM - diameter 400 mm, Frigo-mec F90+SV(M42/R9) liquid receiver with a volume of 47 liter, pressure and safety switches and a control cabinet. The compressor has a displacement of 101,8 m³/h at 50 Hz & 121,3 m³/h at 60 Hz.

*Why choose for HOSBV? We are not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and an industrial cleaning. *Optionally we can also perform a new paint job and arrange the logistics.





