

Bitzer 4G.2

Specifications

Marque	Bitzer
Le type	4G.2
Réfrigérant	Freon
kW at 0°C/+40°C	68
kW at -5°C/+40°C	56,1
kW at -10°C/+40°C	45,8
kW at -20°C/+40°C	29,3
kW at -30°C/+40°C	17,4
kW at -40°C/+40°C	9
Électromoteur Specs	18,5 kW at 1460 RPM
Démarrage à vide	✓
Sur le châssis en acier	✓
Interrupteurs de sécurité	✓
de pression	
Manomètres	✓
Réservoir de liquide	✓
Réservoir de liquide ltr.	89 ltr.
Séparateur d'huile	✓
Panneau de configuration	✓
Remarques	Pulley EM: 220 mm / Compr: 220 mm // Including Head Fan
Remarques	R404a - R22 or other freon types
Tailles	1520x1160x960 mm (LxWxH)



Stock

1

Description

Used Bitzer 4G.2

Used Bitzer 4G.2 freon compressor, complete with unloaded start, pressure safety switches, pressure gauges, oil separator, control panel and liquid receiver with a volume of 89 liters. This unit has a cooling capacity of 68 kW at 0°C/+40°C.

Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also perform a new paint job and arrange the logistics.

