

Bitzer 4H.2 / 6G.2 / 6F.2

Specifications

Marque	Bitzer
Le type	4H.2 / 6G.2 / 6F.2
Réfrigérant	Freon
kW at -10°C/+40°C	190
kW at -20°C/+40°C	124,5
kW at -30°C/+40°C	76,2
kW at -40°C/+40°C	41,5
Électromoteur Specs	16 / 30 / 37
Démarrage à vide	✓
Sur le châssis en acier	✓
Interrupteurs de sécurité	✓
de pression	
Manomètres	✓
Réservoir de liquide	✓
Réservoir de liquide ltr.	20
Séparateur d'huile	✓
Liquid déshydrateur	✓
ligne	
Panneau de configuration	✓
Remarques	# // Electromotor 16 kW at 1445 RPM (4H.2) // 30 kW at 1475 RPM (6H.2) // 37 kW at 1480 RPM (6F.2) // Evaporator Helpman PLV 24-4



	freon types
Remarks	Bitzer 4H.2 / 6G.2 / 6F.2 8400x1700x2500mm (LxWxH)
Stock	1

Description

Used Bitzer 4H.2 / 6G.2 / 6F.2

Used Bitzer 4H.2 / 6G.2 / 6F.2 freon compressor rack, complete with unloaded start, pressure safety switches, pressure gauges, oil separator, liquid line filter drier, control panel and liquid receiver with a volume of 20 liters.

Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and deliver after an industrial cleaning. *If requested we are happy to arrange your logistics.







