

Bitzer 4P (x2)

Specifications

Marque	Bitzer
Le type	4P (x2)
Réfrigérant	Freon
kW at +10°C/+40°C	72,2
kW at 0°C/+40°C	55,1
kW at -5°C/+40°C	42
kW at -10°C/+40°C	34,5
kW at -20°C/+40°C	22,3
kW at -30°C/+40°C	13,5
kW at -40°C/+40°C	7,2
Électromoteur Specs	7,5
Démarrage à vide	✓
Contrôle de capacité	✓
Sur le châssis en acier	✓
Interrupteurs de sécurité de pression	✓
Réservoir de liquide	✓
Séparateur d'huile	✓
Liquid déshydrateur	✓
ligne	
Voyant	✓
Panneau de configuration	✓
Remarques	Electromotor: 7,5 kW at 1450 RPM // Pully EM: 160 mm / Pully compr.: 230 mm



Remarques	R404a – R22 or other freon types
Package / Rack	✓
Tailles	1700x1450x1500 mm (LxWxH)
Stock	1

Description

Used Bitzer 4P (x2)

Used Bitzer 4P (x2) freon compressor rack, complete with unloaded start, capacity control, pressure safety switches, liquid receiver, oil separator, liquid line filter drier, sight glass and control panel.

Why choose for HOSBV? We're not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and deliver after an industrial cleaning. *If requested we are happy to arrange your logistics.





