

Bitzer 4G-30.2 (x1) / 4G.2 (x2)

Specifications

Marque	Bitzer
Le type	4G-30.2 (x1) / 4G.2 (x2)
Réfrigérant	Freon
kW at -5°C/+40°C	201,4
kW at -10°C/+40°C	165,5
kW at -20°C/+40°C	107,9
kW at -30°C/+40°C	65,5
Électromoteur Specs	22
Démarrage à vide	✓
Contrôle de capacité	✓
Sur le châssis en acier	✓
Interrupteurs de sécurité de pression	✓
Manomètres	✓
Réservoir de liquide	✓
Réservoir de liquide ltr.	224
Aspiration d'accumulateur	✓
Séparateur d'huile	✓
Système de niveau d'huile	✓
Liquid déshydrateur ligne	✓
Voyant	✓



	1445 RPM
Remarques	R404a20R224G-30.2) / R408,20R22 (4G.2) //
Package / Rack	Electromotor: 22 kW at
Tailles	2900x2150x1800 mm (LxWxH)
Stock	1

Description

Used Bitzer 4G-30.2 (x1) / 4G.2 (x2)

Compressor unit Bitzer 4G-30.2 (x1) / 4G.2 (x2) with 2 Electromotor Leroy Somer P180M.T (22 kW at 1445 RPM). This used compressor unit has the following components: Liquid Receiver Bitzer F2701N, Oil Separator and more.
*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.
*Optional we can also perform a new paint job and arrange the logistics.





