

Mycom F2520SSC-51

Specifications

Marque	Mycom
Le type	F2520SSC-51
Réfrigérant	NH 3 (ammonia)
kW at -20°C/+40°C	653,6*
kW at -30°C/+40°C	546,5
kW at -40°C/+40°C	311
Électromoteur Specs	250
Démarrage à vide	✓
Contrôle de capacité	✓
Sur le châssis en acier	✓
Interrupteurs de sécurité	✓
de pression	
Manomètres	✓
Séparateur d'huile	✓
Panneau de configuration	✓
Remarques	# // *Capacity based on -25°C/+40°C // Electromotor: 250 kW at 2970 RPM
Package / Rack	✓
Tailles	5000x2100x3000 mm (LxWxH)
Stock	1



Description

Used Mycom F2520SSC-51

Used Mycom F2520SSC-51 screw compressor unit. This unit has the following components: 1x Electromotor Leroy Somer PLS315L-T (250 kW at 2970 RPM), 1x Mycom M50P oil pump, oil separator and control panel.

Compressor unit has run on -45°C/+35°C (300 kW).

*Why choose for HOSBV? Were not only the largest used refrigeration specialist in Europe, but also, we deliver all equipment including an extensive test, warranty and industrial cleaning.

*Optional we can also perform a new paint job and arrange the logistics.







