

Goedhart VC 82507

Specifications

La marque	Goedhart
Type	VC 82507
Capacité kW	24,7
Réfrigérant	Freon
Nombre de ventilateurs	2
Espace Fan in mm	7
Dégivrage	Electric
m ³ /h	13.560
Tailles	2310x980x720 mm (LxWxH)
Remarques	Fan: 450 WATTS / 1360 RPM / Ø = 500 mm
Stock	8



Description

Used Goedhart VC 82507

Used Goedhart VC 82507 // 2x Fans:
WOODS / 450 WATTS / 1360 RPM / Ø =
500 mm / 13560 m³/h



R404A														Refrigerant														
Type VCI	DTI = 10K (C)		DTI = 15K (C)		DTI = 20K (C)		DTI = 25K (C)		DTI = 30K (C)		Air volume m³/h L/s @ 2.5m/s L/s @ 2.0m/s	Surface m² dm²	Internal volume dm³	Weight kg	L	B	H	C	E1	E2	E3	D1	D2	In mm	Out mm	Hot gas mm	Airflow** m³/s	
	kW	kW	kW	kW	kW	kW	kW	kW	kW	kW																		
4.1.40.7	4.0	2.8	3430	52	22	6	76	1156	670	620	500	756	578	15	15	19	20											
6.1.40.7	5.1	3.8	3285	52	33	9	80	1156	770	620	600	756	578	12	15	19	20											
8.1.40.7	6.3	4.5	3147	52	44	11	96	1156	870	620	700	756	578	12	22	19	20											
4.1.45.7	5.5	4.1	5206	56	30	8	93	1256	670	720	500	856	628	12	22	19	22.5											
6.1.45.7	7.7	5.4	4968	56	45	12	97	1256	770	720	600	856	628	12	22	19	22.5											
8.1.45.7	9.2	6.6	4754	56	61	16	116	1256	870	720	700	856	628	12	22	19	22.5											
4.1.50.7	7.8	5.5	7387	63	38	10	115	1456	790	720	600	1056	728	12	22	19	25											
6.1.50.7	10.4	7.5	7073	63	57	15	122	1456	890	720	700	1056	728	12	22	19	25											
8.1.50.7	12.4	8.9	6786	63	76	19	143	1456	990	720	800	1056	728	12	28	19	25											
4.1.56.7	10.1	7.6	10553	63	56	14	160	1556	910	920	700	1156	778	12	22	19	27.5											
6.1.56.7	15.1	10.6	10195	63	84	21	166	1556	1010	920	800	1156	778	12	28	19	27.5											
8.1.56.7	16.7	11.5	9864	63	112	28	193	1556	1110	920	900	1156	778	16	28	19	27.5											
4.1.63.7	14.7	10.5	15095	63	76	19	203	1656	910	1120	700	1256	828	12	28	19	27.5											
6.1.63.7	19.6	14.1	12734	63	114	29	206	1656	1010	1120	800	1256	828	16	35	19	27.5											
8.1.63.7	22.3	16.9	12284	63	152	38	243	1656	1110	1120	900	1256	828	16	35	19	27.5											
4.2.40.7	8.0	5.6	6853	55	44	11	123	1856	670	620	500	1456	928	12	22	19	20											
6.2.40.7	10.7	7.6	6563	55	66	17	130	1856	770	620	600	1456	928	12	22	19	20											
8.2.40.7	12.7	9.0	6285	55	89	22	156	1856	870	620	700	1456	928	12	28	19	20											
4.2.45.7	11.7	8.2	10405	59	60	15	151	2056	670	720	500	1656	1028	12	28	19	22.5											
6.2.45.7	15.3	10.7	9926	59	91	23	160	2056	770	720	600	1656	1028	12	28	19	22.5											
8.2.45.7	18.3	13.2	9495	59	121	30	192	2056	870	720	700	1656	1028	16	28	19	22.5											
4.2.50.7	15.6	11.0	14765	66	76	19	191	2456	790	720	600	2056	1228	16	28	19	25											
6.2.50.7	20.8	14.9	14135	66	114	29	205	2456	890	720	700	2056	1228	16	35	35	25											
8.2.50.7	24.7	17.8	13560	66	152	38	242	2456	990	720	800	2056	1228	16	35	35	25											
4.7.46.7	20.4	14.7	21096	66	111	28	247	2656	910	920	700	2256	1328	16	35	35	27.5											

