

Kuba SPBE 45-G51V

Specifications

La marque	Kuba
Type	SPBE 45-G51V
Capacité kW	6.69
Réfrigérant	Glycol
Nombre de ventilateurs	1
Espace Fan in mm	7
Dégivrage	Electric
m ³ /h	5.650
Tailles	1330x573x662 mm (LxWxH)
Remarques	Fan: 0,4 kW / 1400 RPM / Ø = 450 mm / tube volume 8.3 dm ³ / capacity based on specs SPB 45-F51 and R404A
Stock	2



Description

Used Kuba SPBE 45-G51V

Size: 1330x573x662 mm (LxWxH) ·
Weight: 95 · Fin space: 7 · m³/h: 5.650
· Fans: 1 · Hertz fans: 50 · Rpm: 1400 ·
Refrigerant: Glycol · Brand:
Kuba/Kelvion · Model: SPBE 45-G51 **All
components of this used evaporator
will be tested on good working, leak
free condition (electro engines), coils,
bearings) Choosing HOSBV means
buying with warranty. We perform a
industrial cleaning and rust spots will
be covered. Also, we can arrange your
shipment.





TECHNICAL DATA SPB (E) Küba market SP | Fin spacing 7 mm

Type	Rating Q _a at 50 Hz, DTL R404A	Cooling surface	Air flow	Air throw	Tube volume	Connections	Sound	Fans (Operational values at 50 Hz)
	KW	m ²	m ³ /h	m	dm ³	Inlet / Outlet	L _A / dB(A)	Blade / Current / rpm / W / A
SPB 23-F21	0.9	0.6	2.8	990	7	0.8 10 x10"	12 x10	61 230 230 V-1 1580 30 0.25
SPB 23-F31	1.2	0.8	4.2	890	7	1.3 10 x10"	12 x10	67 230 230 V-1 1580 30 0.25
SPB 30-F21	1.5	1.1	4.3	1660	11	1.3 10 x10"	12 x10	65 300 230 V-1 1360 65 0.30
SPB 30-F31	2.0	1.4	6.4	1550	11	2.2 10 x10"	18 x10	65 300 230 V-1 1360 65 0.30
SPB 35-F21	2.4	1.6	6.6	3040	19	2.1 12 x10"	18 x10	72 350 230 V-1 1430 145 0.68
SPB 35-F31	3.3	2.4	9.8	2940	19	3.0 12 x10"	22 x10	72 350 230 V-1 1430 145 0.68
SPB 35-F41	4.0	2.9	12.8	2820	19	4.1 12 x10"	22 x10	72 350 230 V-1 1430 145 0.68
SPB 45-F31	5.6	4.0	16.7	5070	26	5.2 15 x10"	28 x15	81 450 230 V-1 1360 270 1.20
SPB 45-F41	6.8	5.1	22.1	4870	25	6.8 15 x10"	28 x15	81 450 230 V-1 1360 270 1.20
SPB 45-F51	8.8	6.8	29.6	5880	31	8.3 15 x10"	28 x15	81 450 230 V-1 1400 490 2.71
SPB 45-F71	10.3	7.9	38.4	5270	29	11.7 15 x10"	35 x15	81 450 230 V-1 1400 490 2.71
SPB 23-F32	2.3	1.7	8.4	1780	12	2.5 10 x10"	18 x10	70 230 230 V-1 1580 30 0.25
SPB 30-F32	3.0	2.1	8.6	3320	17	2.7 12 x10"	22 x10	68 300 230 V-1 1360 65 0.30
SPB 30-F32	4.0	2.9	12.8	3380	15	4.1 12 x10"	22 x10	68 300 230 V-1 1360 65 0.30
SPB 35-F32	4.9	3.3	13.2	6080	25	3.9 15 x10"	22 x10	75 350 230 V-1 1430 145 0.68
SPB 35-F32	6.6	4.5	19.5	5880	24	5.9 15 x10"	28 x15	75 350 230 V-1 1430 145 0.68
SPB 35-F42	8.0	5.8	25.8	5640	24	7.8 15 x10"	28 x15	75 350 230 V-1 1430 145 0.68
SPB 45-F32	11.3	8.0	33.4	10020	32	9.9 15 x10"	35 x15	84 450 230 V-1 1360 270 1.20
SPB 45-F42	13.6	10.3	44.3	9740	31	13.3 15 x10"	35 x15	84 450 230 V-1 1360 270 1.20
SPB 45-F52	17.3	13.1	58.1	11300	37	16.1 15 x10"	35 x15	84 450 230 V-1 1400 490 2.71

