

Evapco LRT-3-64

Specifications

La marque	Evapco
Le type	LRT-3-64
Type de produit	Cooling Tower
Capacité kW	239
Nombre de ventilateurs	1
Réfrigérant	Water
Le débit d'air in m³/h	16.920
Tailles	3096x1029x2096 mm (LxWxH)
Remarques	operating weight 1175 // shipping weight 735 // capacity based on Wet bulb temperature 21°C. Entering water temperature 36°C. Leaving water temperature 26°C
Stock	1



Description

Used Evapco LRT-3-64

Size: 3096x1029x2096 mm (LxWxH)
 · m³/h: 16.920 · Fans: 1 · Voltage fans: 400 · Hertz fans: 50 · motorfan 2.2kW
 · Brand: Evapco · Model: LRT-3-64 **All components of this used condensers will be tested on good working, leak free condition (electro engines), condensing block, bearings. Choosing HOSBV means buying with warranty. We perform a industrial cleaning and rust spots will be covered. Also, we can arrange your shipment.



		WEIGHTS (kg)		FANS		DIMENSIONS (mm)			* CONNECTIONS (mm)				
UNIT NO.		Shipping	Operating	No.	HP	W	H	L	Water Inlet	Water Outlet	Make-Up	Drain	Overflow
LRT 3-61	685	1130	1	0.75	3.3	1029	2096	3096	100	100	25	50	50
3-62	690	1130	1	1.5	4.2	1029	2096	3096	100	100	25	50	50
3-63	695	1140	1	2.2	4.8	1029	2096	3096	100	100	25	50	50
3-64	745	1175	1	2.2	4.9	1029	2096	3096	100	100	25	50	50
3-65	745	1180	1	4	5.6	1029	2096	3096	100	100	25	50	50
3-66	755	1195	1	5.5	6.4	1029	2096	3096	100	100	25	50	50
LRT 5-61	1050	1835	1	2.2	7.0	1540	2099	3727	100	100	25	50	80
5-62	1055	1835	1	4	8.3	1540	2099	3727	100	100	25	50	80
5-63	1120	1900	1	2.2	6.9	1540	2403	3727	100	100	25	50	80
5-64	1095	1875	1	4	8.2	1540	2099	3727	100	100	25	50	80
5-65	1075	1860	1	5.5	9.5	1540	2099	3727	100	100	25	50	80
5-66	1090	1870	1	5.5	9.4	1540	2099	3727	100	100	25	50	80
5-67	1125	1910	1	7.5	10.1	1540	2099	3727	100	100	25	50	80
5-68	1145	1925	1	5.5	9.3	1540	2403	3727	100	100	25	50	80
5-69	1160	1940	1	7.5	10.1	1540	2403	3727	100	100	25	50	80
LRT 5-91	1280	2465	1	7.5	12.5	1540	2150	4629	150	150	25	50	80
5-92	1330	2510	1	11	14.3	1540	2150	4629	150	150	25	50	80
5-93	1355	2535	1	11	14.1	1540	2150	4629	150	150	25	50	80
5-94	1360	2540	1	15	15.2	1540	2150	4629	150	150	25	50	80
5-95	1440	2615	1	11	14.0	1540	2454	4629	150	150	25	50	80
5-96	1470	2645	1	15	15.2	1540	2454	4629	150	150	25	50	80

