

Carrier 30 RW 080

Specifications

Merk	Carrier
Type	30 RW 080
Product type	Water Cooled Chiller
Capaciteit kW	80,0
Capaciteit Tons	22,7
Koudemiddel	Freon
Koudemiddel Type	R407C
Gewicht in kg.	761
Afmetingen	2000x870x1800 mm (LxWxH)
Compressor(s) type & model	2x Performer SZ161T4VC
Display	Carrier Pro-Dialog Plus
Opmerkingen	Y.o.b. 2007
Stock	1



Description

Used Carrier 30 RW 080

Gebruikte Carrier 30 RW 080 watergekoelde chiller op R407C. Compleet met 2 Performer SZ161T4VC scroll compressoren, platenwarmtewisselaar als condensor met een watervolume van 9 liter, platenwarmtewisselaar als verdamper met een watervolume van 9 liter en een Carrier Pro-Dialog Plus display.



1 - (FR) NUMERO DE SERIE (EN) SERIAL NUMBER (DE) SERIENNUMMER			12W712823		
2 - MODELE - MODEL MODELLNUMMER			30RW-080-0116-PEE--		
3 - VARIANTE VARIANT VARIANTE			30RW/30RWA		
4 - ANNEE DE FABRICATION ET DATE D'ESSAI YEAR OF MANUFACTURING AND TEST DATE HERSTELLUNGSDATUM UND DATUM			12/09/2007		
5 - FLUIDE - FLUIDE KÄLTEMITTEL			R 407 C		
6 - GROUPE - GROUP GRUPPE			2		
7 - CHARGES CIRCUIT A/B MEDIUM CHARGE A/B KREISLAUF A/B			11.0 Kg / * Kg		
9 - FLUIDE D'INERTAGE INERTING MEDIUM NEUTRALISIERUNG-MEDIUM			23 - AZOTE--NITROGEN--STICKSTOFF		
10 - PRESSION ADMISSIBLE MIN/MAX ALLOWABLE PRESSURE MIN/MAX ZULASSIGE MIN/MAX - DRUCK			21 - HAUTE PRESSION HIGH PRESSURE HOCHDRUCKSEITE		
11 - TEMPERATURE ADMISSIBLE MIN/MAX ALLOWABLE TEMPERATURE MIN/MAX ZULASSIGE MIN/MAX - TEMPERATUREN			22 - BASSE PRESSION LOW PRESSURE NIEDERDRUCKSEITE		
12 - PRESSION DE DECLENCHEMENT DES PRESSOSTATS PRESSURE SWITCH SETTING DRUCKSCHALTER-SOLLDRUCK			(PS) -0.9 / 32.0 bar		
13 - PRESSION DE DECLENCHEMENT DES SOUPAPES SAFETY RELIEF VALVE SETTING SICHERHEITSENTLÜFT-SOLLDRUCK			-0.9 / 25.0 bar		
14 - PRESSION D'ESSAI D'ETANCHETE DE L'UNITE UNIT LEAK TEST PRESSURE LEAKTEST-DRUCK DES GEBÄTS			29.0 bar		
15 - TENSION VOLTAGE SPANNUNG			* bar		
16 - PHASES PHASES PHASEN			25.0 bar		
17 - FREQUENCE FREQUENCY FREQUENZ			15.0 bar		
18 - MAXIMALE MAXIMUM AMP MAXIMAL STROM			400 V		
19 - PUISSANCE ABSORBEE MAX MAX POWER INPUT LEISTUNGSAUFNAHME			~ 50 Hz		
20 - POIDS NET NET WEIGHT NETTOGEWICHT			31.5 / * kW		
24 - PRESSION DE DECLENCHEMENT DES DISQUES DE RUPTURE RUPTURE DISC SETTING EINSTELLDRUCK DER BERTSCHHEIBEN			51.6 / * A		
			761 Kg		
			* bar		
			* bar		



