

Bitzer 4G.2Y (x1) & 4G.2 (x1)

Specifications

Merk	Bitzer
Type	4G.2Y (x1) & 4G.2 (x1)
Koudemiddel	Freon
kW at 0°C/+40°C	141,8
kW at -5°C/+40°C	117,5
kW at -10°C/+40°C	96,3
kW at -20°C/+40°C	62,4
kW at -30°C/+40°C	37,7
kW at -40°C/+40°C	20,2
Onbelaste aanloop	✓
Capaciteits Controle	✓
Op stalen frame	✓
Druk veiligheids	✓
schakelaars	
Manometers	✓
Olie afscheider	✓
Kijk glas	✓
Magneet Afsluiter	✓
m3 / h	204
Opmerkingen	Y.o.b. 1996 - 4G.2 & Y.o.b. 2010 - 4G.2Y
Package / Rack	✓
Afmetingen	1200x1100x750 mm (LxWxH)
Stock	1



Description

Used Bitzer 4G.2Y (x1) & 4G.2 (x1)

Gebruikte Bitzer open-type zuigermotor met 4G.2 & 4G.2Y compressoren op Freon. Compleet met een Rotor XC160L04 elektromotor (x2) - 50 Hz - 15 kW - 1460 tpm, AC&R S-5692X olieafscheider, druk- en veiligheidsschakelaars/meters en kijkglas. De compressors heeft een cilinderinhoud van 204 m³/u bij 1750 tpm.









