

Bitzer 6G.2

Specifications

Merk	Bitzer
Type	6G.2
Koudemiddel	Freon
kW at 0°C/+40°C	106,3
kW at -5°C/+40°C	88,0
kW at -10°C/+40°C	72,2
kW at -20°C/+40°C	46,8
kW at -30°C/+40°C	28,3
kW at -40°C/+40°C	15,2
Onbelaste aanloop	✓
Capaciteits Controle	✓
Op stalen frame	✓
Druk veiligheids schakelaars	✓
Vloeistof tank	✓
Vloeistof tank ltr.	125 l
Kijk glas	✓
m ³ / h	50 Hz - 78,7 m ³ /h / 60 Hz - 153,0 m ³ /h
Afmetingen	2100x780x1260 mm (LxWxH)
Stock	1



Description

Used Bitzer 6G.2

Gebruikte Bitzer 6G.2 open-type zuigercompressor op Freon. Compleet met een VDB 0530 elektromotor - 50 Hz - 30 kW - 1465 RPM, Stahlbau Hopfgarten vloeistofontvanger met een inhoud van 125 liter, druk- en veiligheidsschakelaars en een kijkglas. De compressoren hebben een cilinderinhoud van 50/60 Hz - 78,7/153,0 m³/h - 1450/1750 RPM.





