

## Bitzer 4G-30.2 Y (x2)

### Specifications

|                              |                                                                   |
|------------------------------|-------------------------------------------------------------------|
| Merk                         | Bitzer                                                            |
| Type                         | 4G-30.2 Y (x2)                                                    |
| Koudemiddel                  | Freon                                                             |
| kW at 0°C/+40°C              | 137,2                                                             |
| kW at -5°C/+40°C             | 114,0                                                             |
| kW at -10°C/+40°C            | 94,0                                                              |
| kW at -20°C/+40°C            | 61,4                                                              |
| kW at -30°C/+40°C            | 37,2                                                              |
| kW at -40°C/+40°C            | 19,6                                                              |
| Capaciteits Controle         | ✓                                                                 |
| Op stalen frame              | ✓                                                                 |
| Druk veiligheids schakelaars | ✓                                                                 |
| Manometers                   | ✓                                                                 |
| Olie afscheider              | ✓                                                                 |
| Olie level systeem AC&R      | ✓                                                                 |
| Filter droger                | ✓                                                                 |
| Kijk glas                    | ✓                                                                 |
| Magneet Afsluiter            | ✓                                                                 |
| Schakelkast                  | ✓                                                                 |
| m <sup>3</sup> / h           | 50 Hz - 160,9 m <sup>3</sup> /h / 60 Hz - 203,8 m <sup>3</sup> /h |
| Opmerkingen                  | Y.o.b. 2001                                                       |
| Package / Rack               | ✓                                                                 |
| Afmetingen                   | 2800x1240x3180 mm (LxWxH)                                         |
| Stock                        | 1                                                                 |



### Description

#### Used Bitzer 4G-30.2 Y (x2)

Gebruikte Bitzer 4G-30.2Y (x2) compressor skid op Freon. Compleet met een Witt NDB 559 x 2000 separator, Witt HRP 3232 vloeistofpomp, AC&R S-9108 oliereservoir, Witt HR 3-M/N vlotter, druk- en veiligheidsschakelaars/meters en een schakelkast met een Beijer E300 controller. De compressoren hebben een slagvolume van 160,9 m<sup>3</sup>/h bij 50 Hz & 203,8 m<sup>3</sup>/h bij 60 Hz.

















