

# Bitzer 6G-30.2Y-40P (x2) & 4VCS-6.2Y-40P (x1)

## Specifications

Merk	Bitzer
Type	6G-30.2Y-40P (x2) & 4VCS-6.2Y-40P (x1)
Koudemiddel	Freon
kW at -10°C/+40°C	157,3
kW at -20°C/+40°C	103,1
kW at -30°C/+40°C	66,8
kW at -40°C/+40°C	33,9
Op stalen frame	✓
Druk veiligheids schakelaars	✓
Manometers	✓
Vloeistof tank	✓
Vloeistof tank ltr.	160 l
Olie afscheider	✓
Olie level systeem AC&R	✓
Filter droger	✓
Kijk glas	✓
m3 / h	50 Hz - 288,3 m <sup>3</sup> /h / 60 Hz - 348,1 m <sup>3</sup> /h
Opmerkingen	Y.o.b. 2011
Package / Rack	✓
Afmetingen	3000x1000x2100 mm (LxWxH)
Stock	1



## Description

### Used Bitzer 6G-30.2Y-40P (x2) & 4VCS-6.2Y-40P (x1)

Gebruikte Bitzer 6G-30.2Y-40P (x2) & 4VCS-6.2Y-40P (x1) semi-hermetische zuigercompressor met freon. Compleet met een Bitzer F1602N vloeistofvat met een inhoud van 160 liter, Henry Technologies S-1902-CE olieafscheider, AC&R S-9108-CE oliereservoir, gesoldeerde warmtewisselaar, druk- en veiligheidsschakelaars/-meters en filterdroger voor de vloeistofleiding.









