

Bitzer 6H-25.2Y-40P (x2) & 4DC-7.2Y-40S (x1)

Specifications

Merk	Bitzer
Type	6H-25.2Y-40P (x2) & 4DC-7.2Y-40S (x1)
Koudemiddel	Freon
kW at -5°C/+40°C	166,9
kW at -10°C/+40°C	137,5
kW at -20°C/+40°C	90,1
kW at -30°C/+40°C	54,9
Op stalen frame	✓
Druk veiligheids schakelaars	✓
Manometers	✓
Vloeistof tank	✓
Vloeistof tank ltr.	160 l
Olie afscheider	✓
Olie level systeem AC&R	✓
Filter droger	✓
Kijk glas	✓
m3 / h	50 Hz - 247,9 m ³ /h / 60 Hz - 299,0 m ³ /h
Opmerkingen	Y.o.b. 2004
Package / Rack	✓
Afmetingen	3100x920x2100 mm (LxWxH)
Stock	1



Description

Used Bitzer 6H-25.2Y-40P (x2) & 4DC-7.2Y-40S (x1)

Gebruikte 6H-25.2Y-40P (x2) & 4DC-7.2Y-40S (x1) semi-hermetische zuigercompressor met freon. Compleet met een Bitzer F1602N vloeistofvat met een inhoud van 160 liter, Henry Technologies S-5202-CE olieafscheider, AC&R S-9109-CE oliereservoir, gesoldeerde warmtewisselaar, druk- en veiligheidsschakelaars/-meters en filterdroger voor de vloeistofleiding.







