

# Aermec WRL600

## Specifications

Merk	Aermec
Type	WRL600
Product type	Water Cooled Chiller
Capaciteit kW	140,1*
Capaciteit Tons	39,8
Koudemiddel	Freon
Koudemiddel Type	R410A
Pump	✓
Gewicht in kg.	708 kg
Afmetingen	2070x850x1450 mm (LxWxH)
Compressor(s) type & model	Bitzer GSD80235VAB4-2 (x1) & Bitzer GSD80295VAB4-2 (x1)
Display	Carel pGD1
Opmerkingen	Y.o.b. 2019
Opmerkingen	*Water user side 12°C/7°C; Water source side 0°C/35°C
Stock	1




## Description

### Used Aermec WRL600

Gebruikte Aermec WRL600 watergekoelde chiller op Freon type R410A. Compleet met een Bitzer GSD80235VAB4-2 (x1) & Bitzer GSD80295VAB4-2 (x1) scrollcompressor, gesoldeerde warmtewisselaar als verdamper, gesoldeerde warmtewisselaar als condensor, Ebara 3D/I 40-125/1.5 VAEGG waterpomp, Zilmet 11A Hydro-Pro expansievat met een inhoud van 12 liter en een schakelkast met een Carel pGD1 display.



<b>AERMEC</b>		AERMEC SPA - via Roma, 996 37040 - Bevilacqua(VR) - ITALIA		<b>ERC</b>	<b>EUROVENT</b> CERTIFIED REFRIGERANT	<b>CE</b> 1131
<b>WRL600</b> *****P****		comm/vers. 655710		Prod.date 2019		
400V~3N 50Hz		Serial n. 1905006886920001		IP X0		
30 - 35°C 10/* °C	40 - 45°C 10/* °C	47 - 55°C 10/* °C	12 - 7 °C 30-35 °C			
P <sub>H</sub> [kW] -	P <sub>H</sub> [kW] 160.0	P <sub>H</sub> [kW] -	P <sub>C</sub> [kW] 150.4			
P <sub>E</sub> [kW] -	P <sub>E</sub> [kW] 39.0	P <sub>E</sub> [kW] -	P <sub>E</sub> [kW] 32.6			
COP [W/W] -	COP [W/W]-	COP [W/W] -	EER [W/W] -			
In [A] -	In [A] 72.3	In [A] -	In [A] 64.9			
RES.EL./EL.HEATER	[kW]	Is [A] 316	Imax [A] 117.6			
RES.EL./E-HEIZUNG	Ir [A]	R410A (Kg) 16.8				
TS (HP/LP) [°C]	Min. -10/-30	PS (HP/LP) [bar] 42/30				
	Max. 125/51					
						
WRL600*****P****/1905006886920001						



