

Sabroe SAB 128 HR MK4

Specifications

Merk	Sabroe
Type	SAB 128 HR MK4
Koudemiddel	Freon
kW at +10°C/+40°C	836,6
kW at 0°C/+40°C	580,1
kW at -5°C/+40°C	476,9
kW at -10°C/+40°C	388,2
kW at -20°C/+40°C	294,4
kW at -30°C/+40°C	184,5
kW at -40°C/+40°C	106,6
Onbelaste aanloop	✓
Capaciteits Controle	✓
Op stalen frame	✓
Druk veiligheids schakelaars	✓
Olie afscheider	✓
Magneet Afsluiter	✓
Schakelkast	✓
m ³ / h	106 m ³ /h at 1000 RPM & 615 m ³ /h at 6000 RPM
Opmerkingen	Y.o.b. 2009
Afmetingen	3100x1170x2020 mm (LxWxH)
Stock	1



Description

Used Sabroe SAB 128 HR MK4

Gebruikte Sabroe SAB 182 HR MK4 Rotatune schroefcompressor op R717 (ammoniak). Compleet met een Schorch LN3225M-AB81T-Z elektromotor: 5-101 Hz / 6-132 kW / 247-6005 tpm, Sabroe OHU 4119D olieafscheider, Sabroe OOSI 21142A oliekoeler, 2 Sabroe OF 1606 oliefilters, oliepomp, schakelkast met Unisab 3 en een Vacon frequentieregelaar. De compressor heeft een slagvolume van 106 m³/u bij 1000 tpm en 615 m³/u bij 6000 tpm.









