

Bitzer 4HTC-20KI-40S (x1) & 4FTC-20KI-40P (x2) & 2KHC-05KB-40S (x1) & 2HHC-2KB-40S (x1)

Specifications

Merk	Bitzer
Type	4HTC-20KI-40S (x1) & 4FTC-20KI-40P (x2) & 2KHC-05KB-40S (x1) & 2HHC-2KB-40S (x1)
Koudemiddel	CO2
Refrigerant type	R744
kW at -10°C/+40°C	174,2*
kW at -20°C/+40°C	118,7*
kW at -30°C/+40°C	13,6**
kW at -40°C/+40°C	8,2**
Opmerkingen	*Capacity based on the 4HTC-20KI-40S (x1) & 4FTC-20KI-40P (x2) compressors and a condensing temperature of 10°C
Opmerkingen	**Capacity based on the 2KHC-05KB-40S (x1) & 2HHC-2KB-40S (x1) compressors at a condensing temperature of 0°C
Opmerkingen	Y.o.b. 2013



Package / Rack	✓
Afmetingen	850x3180x2120 mm (LxWxH)
Stock	1

Description

Used Bitzer 4HTC-20KI-40S (x1) & 4FTC-20KI-40P (x2) & 2KHC-05KB-40S (x1) & 2HHC-2KB-40S (x1)

Gebruikt Carrier MINI CCP335-3000+BCM230-3BD0 compressorrack voor CO2 (R744). Compleet met 1 Bitzer 4HTC-20KI-40S & 2 4FTC-20KI-40P & 1 2KHC-05KB-40S & 1 2HHC-2KB-40S semi-hermetische zuigercompressoren. Compleet met een vloeistofvat, Alfa Laval AXP52-72H gesoldeerde warmtewisselaar voor warmteterugwinning, druk- en veiligheidsschakelaars/-meters, schakelkast met 2 frequentieregelaars en bedieningspanelen.











