

# Bitzer 4PC-15.2Y-40P (x2) / 44PC-30.2-40P

## Specifications

|                              |  |
|------------------------------|--|
| Merk                         | Bitzer   |
| Type                         | 4PC-15.2Y-40P (x2) / 44PC-30.2-40P                             |
| Koudemiddel                  | Freon  |
| kW at 0°C/+40°C              | 79,9   |
| kW at -5°C/+40°C             | 66,1   |
| kW at -10°C/+40°C            | 54,1   |
| kW at -20°C/+40°C            | 34,7   |
| kW at -30°C/+40°C            | 20,4   |
| kW at -40°C/+40°C            | 10,1   |
| Capaciteits Controle         | ✓  |
| Druk veiligheids schakelaars | ✓  |
| Kijk glas                    | ✓  |
| Magneet Afsluiter            | ✓  |
| m <sup>3</sup> / h           | 97 m <sup>3</sup> /h at 50 Hz & 117 m <sup>3</sup> /h at 60 Hz |
| Opmerkingen                  | Y.o.b. 2006  |
| Gewicht in kg.               | 302  |
| Afmetingen                   | 1300x500x400 mm (LxWxH)  |
| Stock                        | 1  |



## Description

### Used Bitzer 4PC-15.2Y-40P (x2) / 44PC-30.2-40P

Gebruikte Bitzer 4PC-15.2Y-40P / 44PC-30.2Y-40P tandem semi-hermetische zuigercompressor op freon. Compleet met capaciteitsregeling, druk- en veiligheidsschakelaar en kijkglas. De compressor heeft een slagvolume van 97 m<sup>3</sup>/h bij 50 Hz en 117 m<sup>3</sup>/h bij 60 Hz.



