

Cabero GCHSD089MB/X7S-40 Y V

Specifications

| | |
|----------------------------------|-------------------------------|
| Merk | Cabero |
| Type | GCHSD089MB/X7S-40 Y V |
| Product type | Drycooler |
| Capaciteit kW | 428,9 |
| Aantal Ventilatoren | 14 |
| Toerental Ventilatoren | 770 |
| Koudemiddel | Glycol |
| Luchtstroom in m ³ /h | 214.700 |
| diameter ventilatoren Ø | 800 mm |
| Oppervlakte (m ²) | 3428,3 |
| Inhoud leidingen | 560 |
| Afmetingen | 12650x2360x1750 mm (LxWxH) |
| Opmerkingen | Y.o.b. 2020 |
| Stock | 2 |




Description

Used Cabero GCHSD089MB/X7S-40 Y V

Gebruikte Cabero GCHSD089MB/X7S-40 Y V droge koeler. Compleet met 14 EBM-papst W3G800-HG95-07 ventilatoren - 50/60 Hz - 0,9 kW - 770 tpm - diameter 800 mm, goed voor een totale luchtstroom van 214.700 m³/h. Verder wordt er een schakelkast met Ziehl-Abegg UNIcon ventilatorregeling meegeleverd.



| | | | |
|---|---|--|--------------------------------|
| | | (2) PCN  | CABERO WÄRMETAUSCHER |
| (3) ITEM NO. GCHSD089MB/2X7S-40 Y V (EB) EC AXI A | | | |
| (4) SERIAL NO. 20-NL-5012-2 | (5) DESIGN CODE PED / DIN EN 14276:2 | (6) HEATING SURFACE 3428,3 M ² | |
| (7) FLUID ETHYLENE GLYCOL 30% / WATER 70% | | (8) FLUID GROUP 2 | |
| (9) MAX. ALLOWABLE PRESSURE (PS) 12 BAR | (10) APPLIED PRESSURE TEST (PT) 18 BAR | (11) PRESSURE TEST DATE 29.07.2020 | |
| (12) MIN. MAX. ALLOWABLE TEMP. (TS) -25 °C / +60 °C | (13) VOLUME 560 L | (14) FABRICATION YEAR 2020 | |
| (15) PED CATEGORY / MOD 0/- | (16) ADDITIONAL | | |
| <small>CABERO INDUSTRIAL KFT., KÜLTELEK 22, 7342 MÁGOC, HUNGARY T: +36 72 451-251, F: +36 72 451-020, INFO@CABERO.DE, WWW.CABERO.DE</small> | | | |

