

# Grundfos CRN10-22 A-FGJ-G-E-HQQE

## Specifications

Merk	Grundfos
Type	CRN10-22 A-FGJ-G-E-HQQE
Volumestroom Q max. (m <sup>3</sup> /u)	10,0
Leveringshoogte H max. (M)	225,0
Vermogen max. (kW)	7,5
Stock	2



## Description

### Used Grundfos CRN10-22 A-FGJ-G-E-HQQE

Gebruikte Grundfos CRN10-22 A-FGJ-G-E-HQQE waterpomp met Grundfos MG132SB2-38FF265-H3 elektromotor 50/60 Hz - 7,5 kW - 2910-2920/3490-3530 toeren per minuut. De pomp heeft de volgende specificaties: Qmax: 10,0 m<sup>3</sup>/u - Hmax: 225,0 m - Pmax: 7,5 kW. Afmetingen: 1400x340x350 mm (LxBxH) & 112 kg.



Type	CRN10-22 A-FGJ-G-E-HQQE				
Model	A96501300 P31449				
f	50	Hz	P <sub>2</sub>	7,50	kW
n	2919	min <sup>-1</sup>	H <sub>max</sub>	225	m
Q	10	m <sup>3</sup> /h	H	180.6	m
p <sub>max</sub> /t <sub>max</sub>	25/120	bar/°C	CCW		
Serial No.	0003	Made in Hungary			
MEI ≥	0.57	η <sub>p</sub> (%)	58,9	 <b>GRUNDFOS</b> <small>DK-8850 Bjerringbro, Denmark</small>	



97702205	3~MOT	MG132SB2-38FF265-H3			
	P <sub>2</sub>	7,50 kW	2 - pole/ S1	No.85U17522	
	50Hz	Δ/Y	U 380-415/660-690 V		
			I <sub>1/4</sub> 14,4-14,0/8,30-8,10A		
			I <sub>max</sub> 15,8-15,4/9,15-8,90A		
			cos φ	0,88-0,82	n 2910-2920min <sup>-1</sup>
			Eff. IE3 90,1%		
	60Hz	Δ/Y	U 380-480/660-690 V		
			I <sub>1/4</sub> 14,2-12,0/8,20-8,10A		
			I <sub>max</sub> 15,6-13,2/9,00-8,90A		
		cos φ	0,90-0,82	n 3490-3530min <sup>-1</sup>	
		Eff. IE2 89,5% - IE3 90,2%			

