

Bitzer 4EES-4Y-40S (x2) & 4CE-6.F1Y-40S (x1)

Specifications

| | |
|------------------------------|-------------------------------------------------------------------|
| Merk | Bitzer |
| Type | 4EES-4Y-40S (x2) & 4CE-6.F1Y-40S (x1) |
| Koudemiddel | Freon |
| kW at +10°C/+40°C | 59,1 |
| kW at 0°C/+40°C | 39,4 |
| kW at -5°C/+40°C | 31,6 |
| kW at -10°C/+40°C | 25,1 |
| kW at -20°C/+40°C | 15,1 |
| Op stalen frame | ✓ |
| Druk veiligheids schakelaars | ✓ |
| Schakelkast | ✓ |
| m ³ / h | 77,9 m ³ /h at 50 Hz & 94,0 m ³ /h at 60 Hz |
| Opmerkingen | 4EES-4Y-40S - Y.o.b. 2013 4CE-6.F1Y-40S - Y.o.b. 2019 |
| Package / Rack | ✓ |



| | |
|-------------|--------------------------------------|
| | (LxWxH) |
| Stoeltingen | Compressor rack: 1600x880x1650 mm |
| | (LxWxH) |
| | Control cabinet: 800x350x1050 mm |

Description

Used Bitzer 4EES-4Y-40S (x2) & 4CE-6.F1Y-40S (x1)

Gebruikte Bitzer 4EES-4Y-40S (x2) & 4CE-6.F1Y-40S (x1) semi-hermetische zuigercompressor rack op Freon. Compleet met druk- en veiligheidsschakelaar en schakelkast. De compressoren hebben een totale verplaatsing van 77,9 m³/h bij 50 Hz en 94,0 m³/h bij 60 Hz.





