

Mycom 200VLD-L

Specifications

Merk	Mycom
Type	200VLD-L
Koudemiddel	NH 3 (ammonia)
kW at 0°C/+40°C	1166,6
kW at -5°C/+40°C	958,5
kW at -10°C/+40°C	778,6
kW at -20°C/+40°C	492,8
kW at -30°C/+40°C	288,8
Elektromotor Specs	50/60 Hz - 315 kW - 2970/3565 RPM
Onbelaste aanloop	✓
Capaciteits Controle	✓
Op stalen frame	✓
Olie afscheider	✓
Kijk glas	✓
Schakelkast	✓
Opmerkingen	Y.o.b. 2010
Gewicht in kg.	4750
Stock	1



Description

Used Mycom 200VLD-L

Gebruikte Mycom/Mayekawa 200VLD-L schroefcompressor op NH3 (ammoniak). Compleet met 2EC IE3-0DP-315LX-2 elektromotor - 50/60 Hz - 315 kW - 2970/3565 RPM, Mayekawa HS7533-200-CE olieafscheider met een volume van 1560 liter, Mayekawa OC15245V oliekoeler, Mycom F50P oliepomp, 2 Mycom OFC 50 oliefilters en een schakelkast met een Mayekawa Mypro-CP3 controller.









