

Mycom FM160L-L

Specifications

| | |
|---------------------------------|--|
| Merk | Mycom |
| Type | FM160L-L |
| Koudemiddel | NH 3 (ammonia) |
| kW at +10°C/+40°C | 835,4 |
| kW at 0°C/+40°C | 579,6 |
| kW at -5°C/+40°C | 475,6 |
| kW at -10°C/+40°C | 385,6 |
| kW at -20°C/+40°C | 242,7 |
| kW at -30°C/+40°C | 140,7 |
| Elektromotor Specs | 50/60 Hz - 132/152 kW - 2945/3538 RPM |
| Onbelaste aanloop | ✓ |
| Capaciteits Controle | ✓ |
| Op stalen frame | ✓ |
| Druk veiligheids schakelaars | ✓ |
| Manometers | ✓ |
| Olie afscheider | ✓ |
| Kijk glas | ✓ |
| Schakelkast | ✓ |
| Opmerkingen | Y.o.b. 2008 |
| Gewicht in kg. | 3300 |
| Stock | 1 |



Description

Used Mycom FM160L-L

Gebruikte Mycom/Mayekawa FM160L-L schroefcompressor op skid voor NH3 (ammoniak). Compleet met een Leroy Somer PLS280MC-T elektromotor - 50/60 Hz - 132/152 kW - 2945/3538 RPM, Mayekawa HS 6023 olieafscheider met een volume van 700 liter, Mayekawa OC-15245-V oliekoeler, 2 Mayekawa OFC 50 oliefilters, druk- en veiligheidsschakelaars/meters en een schakelkast met een Mycom MYPRO-CP3 controller.







