

Bitzer 44CC-18.2Y-40S Tandem / 4CC-9.2Y-40S (x2)

Specifications

| | |
|----------------------|---|
| Merk | Bitzer |
| Type | 44CC-18.2Y-40S Tandem / 4CC-9.2Y-40S (x2) |
| Koudemiddel | Freon |
| kW at 0°C/+40°C | 50,7 |
| kW at -5°C/+40°C | 42,2 |
| kW at -10°C/+40°C | 34,8 |
| kW at -20°C/+40°C | 22,8 |
| kW at -30°C/+40°C | 14,0 |
| kW at -40°C/+40°C | 7,5 |
| kW at -45°C/+40°C | 5,1 |
| Capaciteits Controle | ✓ |
| Kijk glas | ✓ |
| m ³ / h | 65,0 |
| Opmerkingen | Y.o.b. 2007 |
| Gewicht in kg. | 186 |
| Afmetingen | 1050x320x400 mm (LxWxH) |
| Stock | 1 |



Description

Used Bitzer 44CC-18.2Y-40S Tandem / 4CC-9.2Y-40S (x2)

Gebruikte Bitzer 44CC-18.2Y-40S tandemcompressor. Compleet met twee Bitzer 4CC-9.2Y-40S semi-hermetische zuigercompressoren en kijkglas. De compressor heeft een verplaatsing van 65,0 m³/h bij 50 Hz en 78,4 m³/h bij 60 Hz.

