

Bitzer 4FC-5.2 Y (x3) & 2CC-4.2 Y (x1) & 2FC-3.2 Y (x1)

Specifications

| | |
|------------------------------|--|
| Merk | Bitzer |
| Type | 4FC-5.2 Y (x3) & 2CC-4.2 Y (x1) & 2FC-3.2 Y (x1) |
| Koudemiddel | Freon |
| kW at 0°C/+40°C | 62,0 |
| kW at -5°C/+40°C | 51,5 |
| kW at -10°C/+40°C | 42,3 |
| kW at -20°C/+40°C | 27,6 |
| kW at -30°C/+40°C | 16,6 |
| kW at -40°C/+40°C | 8,7 |
| kW at -45°C/+40°C | 5,7 |
| Capaciteits Controle | ✓ |
| Op stalen frame | ✓ |
| Druk veiligheids schakelaars | ✓ |
| Manometers | ✓ |
| Olie afscheider | ✓ |
| Olie level systeem AC&R | ✓ |
| Kijk glas | ✓ |
| m ³ / h | 80 |
| Package / Rack | ✓ |
| Afmetingen | 3150x1300x1020 mm (LxWxH) |
| Stock | 1 |



Description

Used Bitzer 4FC-5.2 Y (x3) & 2CC-4.2 Y (x1) & 2FC-3.2 Y (x1)

Gebruikte Bitzer 4FC-5.2 Y (x3), 2CC-4.2 Y (x1) en 2FC-3.2 Y (x1) semi-hermetische zuigercompressor rack op Freon. Compleet met Henry Technologies S-9109-CE olieafscheider, druk- en veiligheidsschakelaars/meters en een AC&R olieniveausysteem. De compressoren hebben een totale verplaatsing van 80,0 m³/h bij 50 Hz en 96,0 m³/h bij 60 Hz.





