

Bitzer 4H.2 / 6G.2 / 6F.2

Specifications

Merk	Bitzer
Type	4H.2 / 6G.2 / 6F.2
Koudemiddel	Freon
kW at -10°C/+40°C	190
kW at -20°C/+40°C	124,5
kW at -30°C/+40°C	76,2
kW at -40°C/+40°C	41,5
Elektromotor Specs	16 / 30 / 37
Onbelaste aanloop	✓
Op stalen frame	✓
Druk veiligheids schakelaars	✓
Manometers	✓
Vloeistof tank	✓
Vloeistof tank ltr.	20
Olie afscheider	✓
Filter droger	✓
Schakelkast	✓
Opmerkingen	# // Electromotor 16 kW at 1445 RPM (4H.2) // 30 kW at 1475 RPM (6H.2) // 37 kW at 1480 RPM (6F.2) // Evaporator Helpman PLV 24-4
Opmerkingen	R404a - R22 or other freon types



	(LxWxH)
Stellingen	3900x1700x2500 mm

Description

Used Bitzer 4H.2 / 6G.2 / 6F.2

Gebruikt Bitzer 4H.2 / 6G.2 / 6F.2 freon compressorrek, compleet met onbelaste start, drukveiligheidsschakelaars, manometers, olieafscheider, vloeistofleiding filterdroger, bedieningspaneel en vloeistofreservoir met een inhoud van 20 liter.







