

Bitzer 4G.2 (x3) / 6F.2 (x1)

Specifications

Merk	Bitzer
Type	4G.2 (x3) / 6F.2 (x1)
Koudemiddel	Freon
kW at +10°C/+40°C	465,2
kW at 0°C/+40°C	303,4
kW at -5°C/+40°C	268,6
kW at -10°C/+40°C	219,5
kW at -20°C/+40°C	140,9
kW at -30°C/+40°C	84
kW at -40°C/+40°C	43,8
Elektromotor Specs	22 / 37
Onbelaste aanloop	✓
Capaciteits Controle	✓
Op stalen frame	✓
Druk veiligheids schakelaars	✓
Manometers	✓
Olie afscheider	✓
Opmerkingen	# // 1x Compr. Bitzer 4G.2 y.o.b. 2007 // Electromotor 4G.2: 22 kW at 1480 RPM // Electromotor 6F.2: 37 kW at 1475 RPM
Opmerkingen	R404a - R22 or other freon types
Package / Rack	✓



Afmetingen	3800x1350x1950 mm (LxWxH)
------------	------------------------------

Stock	1
-------	---

Description

Used Bitzer 4G.2 (x3) / 6F.2 (x1)

Gebruikt Bitzer 4G.2 (x3) / 6F.2 (x1) freon compressorrek, compleet met onbelaste start, capaciteitsregeling, drukveiligheidsschakelaars, manometers en olieafscheider. deze unit heeft een koelcapaciteit van 465,2 kW bij +10°C/+40°C.





