

Bitzer 4P (x2)

Specifications

Merk	Bitzer
Type	4P (x2)
Koudemiddel	Freon
kW at +10°C/+40°C	72,2
kW at 0°C/+40°C	55,1
kW at -5°C/+40°C	42
kW at -10°C/+40°C	34,5
kW at -20°C/+40°C	22,3
kW at -30°C/+40°C	13,5
kW at -40°C/+40°C	7,2
Elektromotor Specs	7,5
Onbelaste aanloop	✓
Capaciteits Controle	✓
Op stalen frame	✓
Druk veiligheids schakelaars	✓
Vloeistof tank	✓
Olie afscheider	✓
Filter droger	✓
Kijk glas	✓
Schakelkast	✓
Opmerkingen	Electromotor: 7,5 kW at 1450 RPM // Pully EM: 160 mm / Pully compr.: 230 mm
Opmerkingen	R404a - R22 or other freon types



Package / Rack	✓
Afmetingen	1700x1450x1500 mm (LxWxH)
Stock	1

Description

Used Bitzer 4P (x2)

Gebruikt Bitzer 4P (x2) freon compressorrek, compleet met onbelaste start, capaciteitsregeling, drukveiligheidsschakelaars, vloeistofontvanger, olieafscheider, vloeistofleiding filterdroger, kijkglas en bedieningspaneel.





